

MIFARE CARD READER



Versatile proximity card reader for time attendance and access control.

Easy-to-use and user-friendly software

Taiwan Original RF ID Card Module

Read Card Distance: 15-20CM

Super Stable

FEUTURES

- World leading brand, Korean industrial design, Blue LCD. World super slim.
- Philips 32 bit embedded Arm system, reliable performance
- Various Verification Method, ID+PW, CARD, CARD+PW, Standard User capacity 8000. Standard record capacity 50000.
- Support user name display. 16 customizable time attendance status. Multimedia voice prompt.
- Support RFID card, Mifare and HID card module optional
- Standard RS232/485 and TCP/IP communication, Wiegand26 and dry contact output.
- Public/personal message display when waving cards, Bell scheduler function
- Support realtime record download and WEB online tracking function.
- Suitable for all kinds of complicated time attendance management. Easy-to-use and user-friendly software

PARAMETERS

Item	Description
Card reader	RFID Card Reader
Support Card	EM4001/4102 memory cards or compatible card, HID (Optional), Mifare (Optional)
Operating Distance	Maximum 20CM
LCD	128 x 64 Stylish blue screen
Operation Time	<1 Sec
Card Capacity	8000People
Transaction Capacity	Card Capacity: 8000pcs, Transaction Records: 50000
Short Message	100, message storage time >= 3000hours under the status of electricity cutoff
Standard Port	RS232, RS485
Working Current	TCP/IP
Communication distance	Maximum 1,200 Meters
Supply Voltage	DC12V
Data transfer velocity	28800 bps
Temperature/Humidity	0°C — 45°C /10%--80%
Physical Dimension	140(w)×190(h)×30(d)mm
Color	Black

SETTING

